



Aritco 7000 Flexi



Aritco 7000 Flexi - for persons and goods

Aritco 7000 Flexi is a version of the Aritco 7000 lift that is intended for both persons and goods. A risk assessment has been conducted to assess the additional risk that will come when using the platform for both persons as well as for goods. Measures to reduce these risks have been taken and they are now implemented for Aritco 7000 Flexi. Aritco 7000 Flexi has its own certificate.

Several advantages offered by Aritco 7000 Flexi:


- Certificate for persons and goods
- Optimal design and size
- Screw/nut system
- 95% recyclable materials
- 'A' rated energy consumption according to VDI4707
- The lowest maintenance and operating costs on the market



Aritco 7000 Flexi




Length Width




Wheelchair Type A and B according to EN 12183/EN 12184.

* National guidelines may apply.




900 x 1040

Hole through floor: 1330x1190 mm
(No door on B-side: 1305x1190)
Platform: 900x1040 mm
Load: 250 kg
Wheelchair: -




900 x 1280

Hole through floor: 1330x1430 mm
(No door on B-side: 1305x1430)
Platform: 900x1280 mm
Load: 410 kg
Wheelchair: Lone user or type A*




900 x 1480

Hole through floor: 1330x1630 mm
(No door on B-side: 1305x1630)
Platform: 900x1480 mm
Load: 410, 500 kg
Wheelchair: A or B with attendant*




1000 x 1280

Hole through floor: 1430x1430 mm
(No door on B-side: 1405x1430)
Platform: 1000x1280 mm
Load: 410 kg
Wheelchair: Lone user or type A*




1000 x 1480

Hole through floor: 1430x1630 mm
(No door on B-side: 1405x1630)
Platform: 1000x1480 mm
Load: 410, 500 kg
Wheelchair: A or B with attendant*




1000 x 1980

Hole through floor: 1430x2130 mm
(No door on B-side: 1405x2130)
Platform: 1000x1980 mm
Load: 500 kg
Wheelchair: A or B with attendant*



1100 x 1480

Hole through floor: 1530x1630 mm
(No door on B-side: 1505x1630)
Platform: 1100x1480 mm
Load: 410, 500 kg
Wheelchair: A or B with attendant, adjacent entry*



1100 x 1580

Hole through floor: 1530x1730 mm
(No door on B-side: 1505x1730)
Platform: 1100x1580 mm
Load: 500 kg
Wheelchair: A or B with attendant, adjacent entry*

Dimensions

Platform width900-1100 mm
Platform length 1040-1980 mm
Travel height 250-13000 mm

Hole through floor width..... 1305-1530 mm
Hole through floor length1190-2130 mm
Top height 2240 mm

Height of door opening...1800, 1900, 2000, 2100 mm
Width of door opening800, 900 mm

Specifications

Drive system: Screw/nut system

Rated speed: max 0.15m/s

Platform control: "Hold to run" The button has to be kept pressed during the ride

Landing control: One-touch call

Technical compliance:

European Machinery Directive 2006/42/EC
European standard EN 81-41

Rated load: 250-500 kg / 2-5 persons

Number of stops: max 6

Number of doors: max 2 doors per floor

Pit: 50 mm (no pit is required when there is a ramp)

Power supply:

1-phase 230V 50Hz/9A/16A slow
3-phase 230V 50Hz/9A/16A slow
3-phase 400V 50Hz/5.2A/16A slow

Emergency lowering: Battery-powered

Control voltage: 24V

Motor: 2.2kW


Standard for Aritco 7000 Flexi:

- Platform with safety edge painted in yellow (RAL 1018).
- Platform with security list mounted behind the platform face-plate painted in yellow (RAL 1018). Valid when having a half height wall.
- Loading information label. The label is placed on the platform with pictograms warning.
- Certificate for persons and goods.



Optional:

- Steel kerb. For extra protection of the platform and the shaft walls a steel kerb can be ordered as an option for Aritco 7000 Flexi. The steel kerb is a 90 mm high steel frame placed on all sided on the platform, except for door sides. It is recommended when using the lift also for goods.



For more information, please, refer to our product catalogue or visit our website. Due to the continuous product development at the company, the information may change without prior notice.

Platinum Lifts Ltd
Henleaze House 13 Harbury Road Bristol BS9 4PN
T: 0800 774 0123 T: 0117 261 0123 Fax: 0844 504 2207
info@platinum-lifts.co.uk www.platinum-lifts.co.uk